

PM9263 Marking

Marking label:

PM9263 – XYZ v1.4-x 3813

Line 1: Part Number:

X = None	64MB SDRAM, 4MB PSRAM
X = 128M	128MB SDRAM, 4MB PSRAM
X = P	64MB SDARAM, 0MB PSRAM
X = P128M	128MB SDRAM, 0MB PSRAM

Y = None	Temp. range 0° +70°C
Y = I	Temp. range -40° +85°C

Z = None	No DataFlash, No SPI Flash
Z = D	Assembled with DataFlash AT45DB321
Z = S	Assembled with SPI Flash AT25DF321

Line 2: Version v1.4, x - assembling variants depending on the current availability of some parts:

Variants	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	
NAND Flash:																														
HY27UF082G2B-TPCB	X				X				X			X	X	X			X	X												
NAND02GW3B2DN6E		X				X	X			X					X															
MT29F2G08AAD-ET			X																											
MT29F2G08AAD				X																										
MT29F2G08ABAEAWP-IT:E								X			X					X									X	X				
K9F2G08U0C-SCB0																				X	X	X	X	X			X	X	X	X
K9F2G08U0C-SIB0																														
NOR:																														
ES29LV320-70WGI	X	X	X	X	X	X	X			X		X																		
EN29LV320BB-70BIP								X	X		X		X	X	X	X	X	X	X	X										
EN29LV320CB-70BIP																					X	X	X	X	X	X	X	X	X	X
SDRAM:																														
H57V2562GTR-60C	X								X			X	X																	
V54C3256164VHI7I		X					X			X																				
MT48LC16M16A2-75-IT			X																											
K4S561632J-UC75				X																										
PT481616HG					X																									
IS42S16320B-7TLI (128MB)						X								X	X											X				

